

MODULA STAKKAbOX 450mm2



APPLICATION: The product is designed for use in both foot way & roadway installations where it provides access to underground ducting.

<p>1.0 PART NUMBER</p> <p>2.0 STANDARD DESCRIPTION</p> <p>3.0 MATERIAL</p> <p>3.1 TEMPERATURE RANGE</p> <p>3.2 VICAT SOFTENING</p> <p>4.0 STANDARD COLOUR</p> <p>5.0 REFERENCE STANDARDS</p> <p>6.0 PACKING</p> <p>7.0 UNIT WEIGHT</p> <p>8.0 DIMENSIONS</p> <p>9.0 INSTALLATION</p> <p>10.0 RELATED PRODUCTS</p> <p>10.1 CHAMBERS BASES</p> <p>10.2 COVERS & FRAMES to EN124</p> <p>10.2.1 B125 CONCRETE INFILL</p> <p>10.2.3 B125 COMPOSITE</p> <p>10.3 CHAMBER FITTINGS</p> <p>10.3.1 PLASTIC</p>	<p>1001013</p> <p>MODULA Stakkabox; Pre-formed ring section 450mm x 450mm clear opening x 155mm deep Comer Polypropylene PPCP C2467, 20% talc filled</p> <p>-40cC to +100oC</p> <p>+148oC</p> <p>Black</p> <p>EN124 B125 & D400 Vertical Loading requirements BS5834.Part4.1993 Side Wall loading for small chambers BS 1247 Part2 Cold Impact test EN 228 Resistance to Petrol and Chemicals EN295-3 Stress Relief BS2782 Part4 Methods 430A to 430D Water Absorption 32 units per pallet. Pallet weight 170.5kG, 1260 units per container (40 foot)</p> <p>5.3kG</p> <p>Please refer to product drawing</p> <p>Please refer to our Field Installation Guide: FIG001</p> <p>1002904 Base, fitted for MODULA, PE, with drainage for 450mm x 450mm chamber</p> <p>??????? Concrete Infill Cover, Steel Raising Frame 450mm x 450mm Clear Opening x 50mm deep</p> <p>1006002 Composite Cover, Steel RaisingFrame 450mm x 450mm Clear Opening</p> <p>1010301 to 1010305 Bell Mouth Duct Entries to fit nominal 89mm to 110mm O/D</p> <p>1010306 Sub-Duct Chamber Entry Connector 55mm long for 40mm O/D duct</p> <p>1010313 Plastic Hook hanger for Chamber Tidy™ service loop organiser</p> <p>1010314 Plastic Wall bracket for Hook Hanger 1010313</p>
--	---