

MODULA STAKKAbOX 750x600mm



APPLICATION: The product is designed for use in both foot way & roadway installations where it provides access to underground ducting.

1.0 PART NUMBER	1001026
2.0 STANDARD DESCRIPTION	Stakkabox; Pre-formed ring section 750mm x 600mm clear opening x 155mm deep
3.0 MATERIAL	Comer Polypropylene PPCP C2467, 20% talc filled
3.1 TEMPERATURE RANGE	-40cC to +100oC
3.2 VICAT SOFTENING	+148oC
4.0 STANDARD COLOUR	Black
5.0 REFERENCE STANDARDS	EN124 B125 & D400 Vertical Loading requirements BS 1247 Part2 Cold Impact test EN 228 Resistance to Petrol and Chemicals EN295-3 Stress Relief BS2782 Part4 Methods 430A to 430D Water Absorption
6.0 PACKING	20 units per pallet. Pallet weight 156.5kG, 756 units per container (40 foot)
7.0 UNIT WEIGHT	7.82kG
8.0 DIMENSIONS	Please refer to product drawing
9.0 INSTALLATION	Please refer to our Field Installation Guide: FIG001
10.0 RELATED PRODUCTS	
10.1 CHAMBERS BASES	1002909 Base, fitted for MODULA, PE, with drainage for 750mm x 600mm chamber
10.2 COVERS & FRAMES to EN124	
10.2.1 B125 DUCTILE IRON	1004041 Ductile Iron Cover and Frame 750mm x 600mm Clear Opening x 50mm deep
10.2.2 B125 CONCRETE INFILL	1005000 Concrete Infill Cover, Steel Raising Frame 750mm x 600mm Clear Opening x 50mm deep
10.3 CHAMBER FITTINGS	
10.3.1 PLASTIC	1010301 to 1010305 Bell Mouth Duct Entries to fit nominal 89mm to 110mm O/D 1010306 Sub-Duct Chamber Entry Connector 55mm long for 40mm O/D duct 1010313 Plastic Hook hanger for Chamber Tidy™ service loop organiser 1010314 Plastic Wall bracket for Hook Hanger 1010313