

## MODULA STAKKAbOX 900x600mm



**APPLICATION:** The product is designed for use in both foot way & roadway installations where it provides access to underground ducting.

<p><b>1.0 PART NUMBER</b></p> <p><b>2.0 STANDARD DESCRIPTION</b></p> <p><b>3.0 MATERIAL</b></p> <p><b>3.1 TEMPERATURE RANGE</b></p> <p><b>3.2 VICAT SOFTENING</b></p> <p><b>4.0 STANDARD COLOUR</b></p> <p><b>5.0 REFERENCE STANDARDS</b></p> <p><b>6.0 PACKING</b></p> <p><b>7.0 UNIT WEIGHT</b></p> <p><b>8.0 DIMENSIONS</b></p> <p><b>9.0 INSTALLATION</b></p> <p><b>10.0 RELATED PRODUCTS</b></p> <p><b>10.1 CHAMBERS BASES</b></p> <p><b>10.2 COVERS &amp; FRAMES to EN124</b></p> <p><b>10.2.1 B125 CONCRETE INFILL</b></p> <p><b>10.2.2 D400 DUCTILE IRON</b></p> <p><b>10.3 CHAMBER FITTINGS</b></p> <p><b>10.3.1 PLASTIC</b></p>	<p>1001100</p> <p>Stakkabox; Pre-formed ring section 900mm x 600mm clear opening x 155mm deep Comer Polypropylene PPCP C2467, 20% talc filled</p> <p>-40oC to +100oC</p> <p>+148oC</p> <p>Black</p> <p>EN124 B125 &amp; D400 Vertical Loading requirements BS 1247 Part2 Cold Impact test EN 228 Resistance to Petrol and Chemicals EN295-3 Stress Relief BS2782 Part4 Methods 430A to 430D Water Absorption</p> <p>20 units per pallet. Pallet weight 171kG, 8.54kG</p> <p>Please refer to product drawing</p> <p>Please refer to our Field Installation Guide: FIG001</p> <p>1002919 Base, fitted for MODULA, PE, with drainage for 900mm x 600mm chamber</p> <p>1005007 Concrete Infill Cover, Steel Raising Frame 900mm x 600mm Clear Opening x 50mm deep</p> <p>1008001 Ductile Iron Cover and Frame 900mm x 700mm Clear Opening x 100mm deep</p> <p>1010301 to 1010305 Bell Mouth Duct Entries to fit nominal 89mm to 110mm O/D</p> <p>1010306 Sub-Duct Chamber Entry Connector 55mm long for 40mm O/D duct</p> <p>1010313 Plastic Hook hanger for Chamber Tidy™ service loop organiser</p> <p>1010314 Plastic Wall bracket for Hook Hanger 1010313</p>
---	---