

L' ULTIMA STAKKAbOX L1



APPLICATION: The product is designed for use in both foot way & roadway installations where it provides access to underground ducting. It is particularly useful in areas where side load is an issue.

1.0 PART NUMBER	1002085
2.0 STANDARD DESCRIPTION	L' ULTIMA Stakkabox; Pre-formed ring section 530mm x 380mm clear opening x 150mm deep
3.0 MATERIAL	SMC (Sheet Moulding Compound) Glass re-enforced Polyester Resin. 15% Glass.
3.1 TEMPERATURE RANGE	-60cC to +160oC
3.2 FIRE RESISTANCE	Low resistance standard Material, Full Class A Material Available
4.0 STANDARD COLOUR	Grey
5.0 REFERENCE STANDARDS	NF P 98-050-1 Chambres de Telecommunications EN124 B125 & D400 Vertical Loading requirements BS5834.Part4.1993 Side Wall loading for small chambers BS 1247 Part2 Cold Impact test EN 228 Resistance to Petrol and Chemicals EN295-3 Stress Relief BS2782 Part4 Methods 430A to 430D Water Absorption
6.0 PACKING	32 units per pallet, 1512 units per 13metre / 40foot truck
7.0 PART WEIGHT	8.4kG
8.0 DIMENSIONS	Please refer to product drawing 1002085
9.0 INSTALLATION	Please refer to our Field Installation Guide: FIG001
10.0 RELATED PRODUCTS	
10.1 CHAMBERS BASES	1002917 Base, fitted for L'ULTIMA, PE, with drainage for 530mm x 380mm chamber
10.2 COVER & FRAMES to EN124	
10.2.1 B125 CONCRETE INFILL	1005011 Concrete Infill Covers, Steel Raising Frame 530mm x 380mm Clear Opening x 50mm deep
10.2.2 C250 DUCTILE IRON	1007000 Ductile Iron Cover, Steel Frame 530mm x 380mm Clear Opening x 50mm deep
10.2.3 D400 DUCTILE IRON	1008010 Ductile Iron Cover, Steel Frame 530mm x 380mm Clear Opening x 80mm deep
10.3 CHAMBER FITTINGS	
10.3.1 PLASTIC	1010301 to 1010305 Bell Mouth Duct Entries to fit nominal 89mm to 110mm O/D 1010306 Sub-Duct Chamber Entry Connector 55mm long for 40mm O/D duct 1010313 Plastic Hook hanger for Chamber Tidy TM service loop organiser 1010314 Plastic Wall bracket for Hook Hanger 1010313
10.3.2 GALVANISED IRON	1010000 to 1010008 Cable Bearer Bracket Wall Type 178mm to 1880mmlong 1010007 to 1010010 Cable Bearer Arm Type136mm to 365mm long 1010013 Locking Pin (for Cable Bearer Arm) 1010014 Step Iron, Bolt On